

Straight Mechanical  
Ferrule - Fully Insulated

## MECHANICAL CONNECTORS

### MF4/6/SHR Connector



#### Principle Application:

Stranded and solid shaped service conductors.

#### Range:

Product Reference (Part Number)	Type	Core C.S.A. (mm <sup>2</sup> )	
		Min	Max
MF4/6/SHR (51810-04)	Moisture Blocked	6*	16

Note: For jointing other core configurations/sizes please contact Sicame Engineering Dept

The **Sicame MF4/6/SHR** mechanical connector is designed for straight connections on stranded, solid, circular or sector shaped service conductor cores.


It comes complete with a factory fitted lower polypropylene shroud and 'snap on' upper shroud thereby providing a fully insulated connector assembly.

**MF4/6/SHR Connector**

**Secondary Application:**

Stranded and solid circular conductors

**Physical Dimensions:**



**Range:**

Product Reference (Part Number)	Dimensions (mm)		
	'A'	'B'	'C'
MF4/6/SHR (51810-04)	70.0	21.0	25.0

**Material:**

Copper Alloy

**Test Specifications:**

BS4579 : Pt 1 : 1970, BS4579 : Pt 3 : 1976

**Fitting Instructions:**

1. Cut the service cables to length and strip the core insulation equal to half the length of connector + 3mm.
2. Thoroughly abrade all conductors to be jointed.
3. Align cores within connector and tighten screws on each side of the connector consecutively, until tight, using a 3mm AF tightening tool.